

CLEAR PRINT PET EASYSTICK

This media support is suitable for any kind of printing machine. Its silicone adhesive improves the application and allows to remove the product.



SOLAR SCREEN® Warranty
5 YEARS



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	40 %
Visible light transmission	90 %

FRONT

Technology	PET
Thickness	140 µm
Finish	Ultra Clear

COMPATIBILITY

Surface(s)	Flat surface
Application type	Indoor
Printing method	UV - UV gel - Aqueous print - Latex - Eco solvent

DURABILITY

Outdoor resistance	2 years
Indoor resistance	10 years
Anti-scratch/hard coat	No

ADHESIVE


Type	Silicon
Performance	Removable & repositionable

LINER

Type	Mat PET
Thickness	90µ

CONSTRUCTION

1. Special printing coating
2. High optical quality polyester
3. Silicone adhesive, allowing fast dry installation, easy on, easy off
4. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.