



### CLEAR PRINT PET

Clear Print PET films can be printed upon using a UV printing machine. On the other hand, it absorbs more than 95% of all UV-Rays and protects against impacts.



SOLAR SCREEN® Warranty  
**5 YEARS**



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



European Standard EN 12600  
**2B2**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **122 cm**

↔ **152 cm**

### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	<1 %
Visible light transmission	90 %

#### FRONT

Technology	PET
Thickness	50 µm
Finish	Glossy/Ultra Clear

#### COMPATIBILITY

Surface(s)	Flat surface
Application type	Indoor
Printing method	UV - UV gel

#### DURABILITY

Outdoor resistance	2 years
Indoor resistance	15 years
Anti-scratch/hard coat	Yes

#### ADHESIVE

Type	PS adhesive
Performance	Semi-permanent

#### LINER


Type	Clear PET
Thickness	50µ

### APPLICATIONS

Glass surface  
 Showcase  
 Advertising  
 Decoration  
 Urban advertising  
 Exhibitions

### CONSTRUCTION

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
4. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*