



### MAT ACID-X

Mat Acid-X privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.



SOLAR SCREEN® Warranty  
See the notice "new guarantees for the external films"



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **122 cm**

↔ **152 cm**

### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	> 25 %
Visible light transmission	60 %

#### FRONT

Technology	CAST PVC
Thickness	70 µm
Finish	Opalescent

#### COMPATIBILITY

Surface(s)	Flat surface
Application type	Outdoor/indoor
Printing method	UV - UV gel - Aqueous print - Latex - Eco solvent - Solvent

#### DURABILITY

Outdoor resistance	8 years
Indoor resistance	15 years
Anti-scratch/hard coat	No

#### ADHESIVE


Type	Acrylic solvent
Performance	Semi-permanent

#### LINER

Type	Cardstock
Thickness	120µ

### CONSTRUCTION

1. 75µ "cast" polymer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Paper release liner allowing digital cutting



### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*