

#### RASPBERRY C

Applied to clear glass, the transparent Raspberry C film bestows a red/pink tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.



SOLAR SCREEN® Warranty

**5 YEARS** 



Fire-resistance rating **M1** 



Storage from -5°C to +40°C

**¥** 3 YEARS



REACH RoHS compliant

RESPECTED

### WIDTHS AVAILABLE:



152 cm

## TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	22 %
Reflection of external visible light	10 %
Reflection of internal visible light	10 %
Total solar energy rejected	36 %
Total solar energy rejected 2*	32 %
Solar ratio:	
Solar energy reflection	11 %
Solar energy absorption	47 %
Solar energy transmission	42 %
Reduction in Solar Glare	80 %
g-value	0.69
u-value	5.7
Shading coefficient	
Installation type: Interior	
Roll length	30,5 m
Film composition	PET
Thickness	$40~\mu$

# Colour from the outside: RASPBERRY

**CONSTRUCTION** 


### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*\*

Clear single pane	<b>~</b>
Tinted single pane	Ţ
Reflective tinted single pane	<b>~</b>
Clear double pane	Ţ
Tinted double pane	!
Reflective tinted double pane	<b>~</b>
Gas-filled double pane - Low E	Ţ
STADIP EXT. clear double pane	Ţ
STADIP INT. clear double pane	×

✓ Yes 【Caution ➤ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.



# MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.