



ULTIMA 40

Ultima 40 Film is a microperforated adhesive on which a high print quality can be produced. It is suitable for both automotive bodies and glass surfaces. Thanks to its structure, a maximum brightness is maintained (40% VLT). Its white printable side protects you from prying eyes and the black inside allows you to always have a perfect outward view.



SOLAR SCREEN® Warranty
2 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

| | |
|----------------------------|------|
| Ultraviolet transmission | 50 % |
| Visible light transmission | 40 % |

FRONT

| | |
|------------|-----------------------------|
| Technology | Monomeric PVC |
| Thickness | 140 µm |
| Finish | Micro-perforated warm white |

COMPATIBILITY

| | |
|------------------|---|
| Surface(s) | Flat surface |
| Application type | Outdoor/indoor |
| Printing method | UV - UV gel - Aqueous print - Latex - Eco solvent - Solvent |

DURABILITY

| | |
|------------------------|----------|
| Outdoor resistance | 5 years |
| Indoor resistance | 10 years |
| Anti-scratch/hard coat | No |

ADHESIVE


| | |
|-------------|-----------|
| Type | Acrylic |
| Performance | Removable |

LINER

| | |
|-----------|-----------|
| Type | Cardstock |
| Thickness | 160µ |

CONSTRUCTION

1. 100µ monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.